

Salzstraße 11 / 07551 Gera / Phone +49 (0) 365.73 73 20 / Fax +49 (0) 365.3 72 60  
 info@schneider-spezialmontage.de / www.schneider-spezialmontage.de



## MAN 26.430 HGV



### SPECIFICATIONS

- Curtain side HGV mainly used to transport devices and equipment
- To drive on to it using a forklift, electric cranes, etc., the rear end is sloped and two moveable ramps are installed securely

TECHNICAL DATA	
TYPE	MAN 26.430
LENGTH	9,700 mm
WIDTH	2,550 mm
HEIGHT	4,000 mm
CONSTRUCTION	<ul style="list-style-type: none"> <li>- Usable dimensions 6,900 mm x 2,400 mm x 2,850 mm</li> <li>- Comprises rear shutter, side slider and Edscha</li> <li>- chassis behind the rear axle, sloped to 1,750 x 180 mm</li> </ul>
RAMPS	<ul style="list-style-type: none"> <li>- Two ramps, each L 2,950 mm x W 950 mm, moveable</li> <li>- Elector-hydraulic drive</li> </ul>
GROSS WEIGHT	25,700 kg
EMPTY WEIGHT	10,950 kg
PAYLOAD	14,750 kg
COMBINATION VARIANTS	<ul style="list-style-type: none"> <li>- Operation with Kotschenreuther trailer</li> <li>- Transport can be carried out with a total train weight of up to 40 t</li> <li>- Loading weight differences that go beyond this must be approved</li> </ul>

**MAN 26.420 HG**

Examples based on our practical experience  
Extended depictions

